





Installation Instructions -
 JLT SERIES II Cold Air Intake
 2011-18 5.7 L Charger, Challenger, 300C
 (Excluding Shaker Hood models)

#CAI 2-DH57-11; # CAI 2-DH57-11-P; # CAI 2-DH57-11-HC




Thank you for purchasing our product. We hope you are satisfied with the look and performance. If you have any questions, please feel free to call us first before going to the internet. Take your time and it will be a smooth install.

Please review complete instructions prior to installing.

We find it easiest to install the kit as a complete assembly; however, it can be done one piece at a time. Here is a walk through:

Step#	
1	Verify you have all of the following parts included in the kit: (1) JLT Plastic Intake tube, (1) 4"-3.5" 90° Rubber Elbow, (1) 5"x7" Air Filter, (1) JLT Heat Shield, (1) 64 Clamp, (1) 56 Clamp, (1) PVC hose w/fitting, (1) hole plug
2	Gather all of the following tools needed for the installation: 5/16 Nut Driver, 8mm Socket and Ratchet
3	Remove the engine cover by pulling up and remove the stock intake from the throttle body to the airbox. There is only one bolt on the airbox and the clamp at the throttle body. Unplug IAT sensor and PCV line. Now remove the assembly from the car. 
4	Remove the rubber location grommet from the stock air box and install into the hole in the apron. Use stock bolt and install JLT Heat Shield. 

TIP: Remove the 10mm bolts holding the coolant tank and move back for more room.

	<p>Push JLT shield into the location grommet, use the factory bolt and secure to the car. Use supplied plug to fill hole in shield.</p> 
5	<p>Remove IAT sensor from stock tube and insert into hole in the rubber elbow. TWIST and PULL.</p> 
6	<p>Install air filter and 90* rubber elbow onto the tube and install onto the throttle body.</p>
7	<p>Plug in IAT sensor and use supplied hose and fitting to connect PCV.</p>
8	<p>Rotate the tube so the filter is low in the shield and HAND tighten all clamps.</p>
9	<p>Reinstall engine cover.</p> 

Oil Filter: The frequency you should clean your filter will depend on your driving conditions. It is recommended to check your filter at every oil change or 3,000 miles. If there is a build up of dirt as thick as the wire mesh, then it's time to clean your filter. As dirt builds up on your filter, the restriction of the airflow also increases. More frequent cleanings will improve your fuel economy and your vehicle's performance.

To properly clean your oil filter, we recommend the S&B Precision Cleaning & Oiling Kit (located in the Parts Sold Separately Section of our website, www.JLTtruecoldair.com).

Thanks for the business. If you have any questions, please e-mail info@JLTtruecoldair.com or call 757-335-1940. Our hours are Monday-Friday. 8:00am – 5:00pm Eastern Time.

Warranty: JLT Performance Inc. will repair or replace any part of their product found upon our inspection to be defective in workmanship or material within 1 year from the purchase date for the original purchaser.

Disclaimer: JLT Performance Inc. makes no warranties whatsoever, expressed or implied, oral or written to any purchasers, except the warranty above. JLT Performance Inc. hereby specifically excludes from any implied warranty of merchantability or implied warranty of incidental, secondary, or consequential damages of any kind whatsoever. All purchasers and users of products manufactured by JLT Performance Inc. agree to hold harmless and indemnify JLT Performance Inc. from any and all claims arising from their use. Failure to receive notice of any of the limitations contained in this disclaimer shall not serve to extend liability to JLT Performance Inc. for any claims arising out of use of its products.

Custom Paint Disclaimer: All custom paint jobs are done by JLT Performance Inc. Every job is different and done by hand. By ordering a custom paint job, you accept this fact and cannot hold JLT Performance liable for the end result not being exactly what you had in your mind.

Return Policy: All returns will be subject to a 10%-25% restocking fee. Air Filters will not be accepted for return unless they are in original plastic sealed bag. Please visit www.JLTtruecoldair.com for complete return policy.